Intensity

Intensity curves

- **Stimulus/Response - Perception**
- **Input/Output - Gamma**

Quantization

- **Uniform quantization**
- **Non-uniform quantization**

Dithering and halftoning

- **Random dither**
- **Ordered dither**
- **Clustered dither or halftone**
- **Error diffusion**

Copyright © Pat Hanrahan

Measuring Light and Color

Physics: Radiometry

- **The amount of *power* per wavelength interval**

  Termed *radiance*, we will often use *intensity*

Psychophysics: Photometry, latter colorimetry

- **The relative brightness of a light source (color or black/white) when compared to a standard candle**

  Termed *luminance*

- **Uniform perceptual scale**

  Termed *lightness*

Copyright © Pat Hanrahan

Perception of Intensities

Steven's Law:

Sensation (S) vs. Intensity (I)

$$S = I^p$$

Experiments

Sense	Exponent
Brightness	0.33
Smell	0.55
Loudness	0.60
Taste	0.80
Length	1.00
Heaviness	1.45

Stevens $B = I^{1/3}$

Weber $JND = \frac{\Delta I}{I} \approx 0.01$

Fechner $B = k \log I$

Copyright © Pat Hanrahan

Contrast

Contrast: $\Delta I/I$

- **Human vision: 100:1**
- **Printed page: 10:1**
- **Film, photographs, monitors: 80:1**
- **Typical viewing conditions: 5:1**



10%



Adapted from Poynton 1996

Copyright © Pat Hanrahan

Monitor Gamma



$$I = g \cdot (V - V_b)^{\gamma}$$

Monitor
γ=2.5

Two knobs
Black Level (Brightness): V_b
Picture (Contrast): g

Adjustments
1st adjust to full black
Picture 0, adjust black-level
2nd adjust brightness

Copyright © Pat Hanrahan

Monitor + Perception = Linear



Amazing coincidence!

Copyright © Pat Hanrahan

Coding in Perceptual Space

Relative brightness in intensity

- **ΔI 25 to 26 -> ΔB = 4%**
- **ΔI 100 to 101 -> ΔB = 1%**
- **ΔI 200 to 201 -> ΔB= .5%**



Number of levels

- **log 100 / log 1.01 = 463**

NTSC Television



Camera γ=.45 **Monitor γ=2.5**

Copyright © Pat Hanrahan

Perceptual vs. Intensity Space

Perceptual Space

- **+ good distribution of values**
  - **more perceivable intensities and saturated colors**
- **+ optimal compression**
  - **bits used more effectively**
  - **less sensitivity to noise**

Intensity Space

- **- bad distribution of values**
  - **fewer perceivable intensities and colors**
- **+ Easier to compute in**
  - **blending, dithering, antialiasing, lighting, ...**

Copyright © Pat Hanrahan

Gamma Correction

Goal: Operate in linear intensity space

How: Gamma correction table

$$I = V^{\gamma}$$

$$V = P^{1/\gamma}$$

$$I = V^{\gamma} = \left(P^{1/\gamma}\right)^{\gamma} = P$$

Input	Output
0	0
1	16
2	23
3	28
4	32
...	...
...	...
251	253
252	253
253	254
254	254
255	255

Checkerboard test:

What's wrong with this table?

Copyright © Pat Hanrahan

Quantization

Definition: The process of turning a high precision number into a low precision number

Why?

- **Conserve memory**
- **Binary output devices**

How?

- **Minimize error (better, perceptual error)**
- **Distribute error spatially**

Copyright © Pat Hanrahan

Uniform Quantization

Uniform map: $\hat{v} = trunc((K-1)v + 0.5)$

$$0 \le v < 1$$

$$0 \le \hat{v} < K$$








K=256 **K=16** **K=4** **K=2**

Notice contouring

Copyright © Pat Hanrahan

Quantization Error

Quantization introduces error

$$E^2 = \sum_{(x,y)} \left(\frac{\hat{v}(x,y)}{K-1} - v(x,y)\right)^2$$

To reduce error:

1. **Optimal quantization (minimize error)**
2. **Dithering (trade-off intensity/space error)**

Copyright © Pat Hanrahan

Non-uniform Quantization



Image courtesy Don Mitchell

Histogram of Intensities



$$E^2 = \sum_{k=1}^{K} \int_{v_{k-1}}^{v_k} (v - \hat{v}_k)^2 p(v) dv$$

Copyright © Pat Hanrahan

Least-Squares Optimization

$$E^2 = \sum_{k=1}^{K} \int_{v_{k-1}}^{v_k} (v - \hat{v}_k)^2 p(v) dv$$

Least Squares

Means: $\hat{v}_k = \dfrac{\int_{v_{k-1}}^{v_k} v p(v) dv}{\int_{v_{k-1}}^{v_k} p(v) dv}$

Intervals: $\bar{v}_k = \dfrac{1}{2}(\hat{v}_{k-1} + \hat{v}_k)$



Necessary conditions, not an algorithm

Copyright © Pat Hanrahan

K-Means Algorithm



Copyright © Pat Hanrahan

Dithering and Halftoning

Trade spatial for intensity resolution

- **Random dither; Robert's algorithm**
- **Ordered dither**
- **Clustered dither or halftones**
- **Error diffusion**

Your eye will average over an area

Copyright © Pat Hanrahan

Robert's Algorithm

First add noise $\hat{v}(x,y) = trunc(K \times v(x,y) + noise(x,y))$

Then quantize $0 \le noise < 1$



Moves low frequency (average error) to high frequency

Pink(low), *Blue (high),* White(all) frequency noise

Copyright © Pat Hanrahan

Pink vs. Blue Noise

Copyright © Pat Hanrahan

Noise

Noise functions

- **Some noise better than others: blue, ordered**
- **Random function vs random sequence**
- **Reproducible and order independent**
- **Precompute and store in a table (fast on the fly)**
- **Small tiled patterns sufficient**

```
for(y=0; y<ny; y++)
  for(x=0; x<nx; x++)
    vq[x][y] =
      (v[x][y]<threshold[x%M][y%M]) ? 0 : 1;
```


Copyright © Pat Hanrahan

Bayer Ordered Dither Patterns

$$D_2 = \begin{bmatrix} 0 & 2 \\ 3 & 1 \end{bmatrix}$$

$$D_n = \begin{bmatrix} 4D_{n/2}+0 & 4D_{n/2}+2 \\ 4D_{n/2}+3 & 4D_{n/2}+1 \end{bmatrix}$$

$$D_4 = \begin{bmatrix} 0 & 8 & 2 & 10 \\ 12 & 4 & 14 & 6 \\ 3 & 11 & 1 & 9 \\ 15 & 7 & 13 & 5 \end{bmatrix}$$



Copyright © Pat Hanrahan

Magic Squares



$$M_4 = \begin{bmatrix} 0 & 6 & 13 & 11 \\ 9 & 15 & 4 & 2 \\ 14 & 8 & 3 & 5 \\ 7 & 1 & 10 & 12 \end{bmatrix}$$



$$P_4 = \begin{bmatrix} 15 & 8 & 5 & 2 \\ 4 & 3 & 14 & 9 \\ 10 & 13 & 0 & 7 \\ 1 & 6 & 11 & 12 \end{bmatrix}$$

Copyright © Pat Hanrahan

Comparison

Blue Noise



Ordered Dither

Copyright © Pat Hanrahan

Classic Halftoning

Printers: *Binary Blobs* of ink

- **Clustered pattern**
- **Enlarging spot**

Classical printer screens

- **Spot function**
- **Line frequency**
- **Tilt angle**



Copyright © Pat Hanrahan

Line Screens



line 10 angle 0



line 10 angle 45

Frequency Sensitivity



45 degrees best

Copyright © Pat Hanrahan

Line Screens

High spatial resolution means low intensity resolution



line 100 angle 45



line 200 angle 45

Copyright © Pat Hanrahan

Error Diffusion

Idea: Quantize, then distribute error to neighbors

```
for(y=0; y<ny; y++)
  for(x=0; x<nx; x++){
    vq[x][y] = quantize(v[x][y]);

    e = v[x][y] - vq[x][y];

    i[x+1][y] += 3/8*e;
    i[x][y+1] += 3/8*e;
    i[x+1][y+1] += 1/4*e;
}
```



Copyright © Pat Hanrahan

Comparison



Blue Noise **Bayer Dither** **Floyd-Steinberg**

Copyright © Pat Hanrahan